



09-15-00

A

# UTILITY PATENT APPLICATION TRANSMITTAL

Only for nonprovisional applications under 37 CFR § 1.53(b)

Attorney Docket No.

859063.478

First Inventor or Application Identifier

Marc Laury

Title

ERROR DISTRIBUTION FOR THE APPROXIMATION  
OF THE PIXEL COLOR OF A DIGITAL IMAGE

Express Mail Label No.

EL615483535US

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

## ADDRESS TO:

Box Patent Application  
Assistant Commissioner for Patents  
Washington, D.C. 202311. ☒ General Authorization Form & Fee Transmittal  
(Submit an original and a duplicate for fee processing)2. ☒ Specification [Total Pages] **15**  
(preferred arrangement set forth below)

- Descriptive Title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

☒ Drawing(s) (35 USC 113) [Total Sheets] **2**4. ☒ Oath or Declaration [Total Pages] **4**

- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d))  
(for continuation/divisional with Box 17 completed)
- i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting  
inventor(s) named in the prior application,  
see 37 CFR 1.63(d)(2) and 1.33(b)

Incorporation By Reference (useable if box 4b is checked)  
The entire disclosure of the prior application, from which a  
copy of the oath or declaration is supplied under Box 4b,  
is considered to be part of the disclosure of the  
accompanying application and is hereby incorporated by  
reference therein.

6. ☐ Microfiche Computer Program (Appendix)7. Nucleotide and Amino Acid Sequence Submission  
(if applicable, all necessary)

- a. ☐ Computer-Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney10. ☐ English Translation Document (if applicable)11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations12. ☐ Preliminary Amendment13. ☒ Return Receipt Postcard14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application, Status still proper and desired15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)16. ☒ Other: Certificate of Express Mail  
Check

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary amendment

☐ Continuation ☐ Divisional ☐ Continuation-In-Part (CIP) of prior Application No.: \_\_\_\_\_

Prior application information: Examiner \_\_\_\_\_ Group / Art Unit \_\_\_\_\_

☒ Claims the benefit of French Application No. 99/11607 filed September 14, 1999

## CORRESPONDENCE ADDRESS

Robert Iannucci  
Seed Intellectual Property Law Group PLLC  
701 Fifth Avenue, Suite 6300  
Seattle, Washington 98104-7092  
Phone: (206) 622-4900  
Fax: (206) 682-6031

Respectfully submitted,

TYPED or PRINTED NAME Robert IannucciSIGNATURE [Signature]REGISTRATION NO. 33,514Date 9/13/00

U:\bobi\sgs\859063\478\02-ptosb05\

PATENT

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



Applicants : Marc LAURY – Grenoble, France  
 Franck SEIGNERET – Rives, France  
 Emmanuel CHIARUZZI – Grenoble, France

Title : ERROR DISTRIBUTION FOR THE APPROXIMATION OF THE  
 PIXEL COLOR OF A DIGITAL IMAGE

Docket No. : 859063.478

Date : September 13, 2000

Box Patent Application  
 Assistant Commissioner for Patents  
 Washington, DC 20231

GENERAL AUTHORIZATION UNDER 37 C.F.R. § 1.136(a)(3)AND FEE TRANSMITTAL

Assistant Commissioner for Patents:

With respect to the above-identified application, the Assistant Commissioner is authorized to treat any concurrent or future reply requiring a petition for an extension of time under 37 C.F.R. § 1.136(a)(3) for its timely submission as incorporating a petition therefor for the appropriate length of time. The Assistant Commissioner is also authorized to charge any fees which may be required, or credit any overpayment, to Deposit Account No. 19-1090.

With respect to the above-identified application, the fee is calculated below:


For	Number filed	Number extra		Rate		
Basic Fee						\$ 690
Total Claims	20	0	X	\$	=	\$ 0
Independent Claims	3	0	X	\$	=	\$ 0
Multiple Dependent Claim					+	\$ 0
Assignment Fee					+	\$ 40
<b>TOTAL FILING FEE</b>						<b>\$ 730</b>

A check in the amount of \$730 is enclosed to cover the filing fee.

The Assistant Commissioner is authorized to charge any fees under 37 C.F.R. §§ 1.16 and 1.17 which may be required, or credit any overpayment, to Deposit Account No. 19-1090. A duplicate copy of this request is enclosed.

Date

9/13/00

  
Robert Iannucci  
Registration No. 33,514

RXI:lm

Seed Intellectual Property Law Group PLLC  
701 Fifth Avenue, Suite 6300  
Seattle, Washington 98104-7092  
Phone: (206) 622-4900  
Fax: (206) 682-6031

U:\bobi\sgs\859063\478\03-general authorization.doc

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PATENT

Applicants : Marc LAURY – Grenoble, France  
Franck SEIGNERET – Rives, France  
Emmanuel CHIARUZZI – Grenoble, France  
Filed : September 13, 2000  
For : ERROR DISTRIBUTION FOR THE APPROXIMATION OF THE  
PIXEL COLOR OF A DIGITAL IMAGE



Docket No. : 859063.478  
Date : September 13, 2000


Box Patent Application  
Assistant Commissioner for Patents  
Washington, DC 20231

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Assistant Commissioner for Patents:

I hereby certify that the enclosures listed below are being deposited with the United States Postal Service "EXPRESS MAIL Post Office to Addressee" service under 37 C.F.R. § 1.10, Mailing Label Certificate No. EL615483535US, on September 13, 2000, addressed to Box Patent Application, Assistant Commissioner for Patents, Washington, DC 20231.

Respectfully submitted,  
Seed Intellectual Property Law Group PLLC

  
Laura Turner

Enclosures:

Postcard  
Check  
Form PTO/SB/05  
General Authorization Under 37 C.F.R. § 1.136(a)(3) and Fee Transmittal (+ copy)  
Specification, Claims, Abstract (15 pages)  
2 Sheets of Drawings (Figures 1-6)  
Declaration and Power of Attorney  
Form PTO-1595  
Assignment  
Information Disclosure Statement, Form PTO-1449, and Cited References (3)  
U:\bobi\sgs\859063\478\01-cert of express mail.doc

SCAN 3

## ERROR DISTRIBUTION FOR THE APPROXIMATION OF THE PIXEL COLOR OF A DIGITAL IMAGE

### TECHNICAL FIELD

The present invention relates to the processing of digital images and in particular to the reduction of the colors of a digital image to the colors of a color look-up table of reduced size.

### BACKGROUND OF THE INVENTION

A digital image is conventionally formed of pixel rows and columns. Each pixel, located by an abscissa and an ordinate, is in particular associated with a color. The colors of all pixels of a same image are conventionally coded with a same number of bits, this number determining the number of possible colors for each pixel. As an example, a coding (called RGB coding) is considered, in which the colors are represented by three components: red (R), green (G), and blue (B), each of which is coded over eight bits. Such a coding enables describing  $2^{3 \times 8}$ , that is, more than 16 million different colors.

Fig. 1 very schematically shows a fragment of a digital image 2, organized in pixel lines and columns. Each pixel  $i$  of image 2 is located by an abscissa  $X(i)$  and an ordinate  $Y(i)$ , and is associated with a color  $RGB(i)$ . In Fig. 1, the two first pixels 0 and 1 of the first line of image 2 have been shown. Considering that image 2 is organized in lines of  $n$  pixels, the two first pixels of the second image line are designated by  $n$  and  $n+1$ . An example of color coded over 24 bits has been associated with each of the shown pixels. For clarity, each of components  $R(i)$ ,  $G(i)$ , and  $B(i)$  is shown in hexadecimal. Pixel 0 has a color  $RGB(0) = F11$ , pixel 1 has a color  $RGB(1) = 1A1$ , pixel  $n$  has a color  $RGB(n) = 1B0$ , and pixel  $n+1$  has a color  $RGB(n+1) = CE0$ .

In certain applications, it may be desired to reduce the number of bits associated with the colors of a digital image. An image of a given number of pixels having its colors coded over a large number of bits represents a large number of bits, and reducing

this number may enable storing the image in a reduced memory space or transmitting it, for example with a modem, in a shorter time.

A known solution consists of creating a look-up table, or color look-up table (CLUT) containing a restricted number of colors coded like the original colors of the pixels. Each pixel then is associated with an address chosen in the look-up table, which corresponds to the CLUT color that is closest to its original color.

Fig. 2 schematically shows a circuit 4 enabling performing an approximation such as described hereabove of the color of the pixels of an image. Circuit 4 includes a memory (MEM) 6 in which are stored the CLUT colors and an evaluation circuit (EVAL) 8, a first input of which receives the CLUT colors, and a second input of which successively receives the original color of each pixel. For the type of coding taken as an example, if  $R_p$ ,  $G_p$ , and  $B_p$  are the components of a color of the look-up table, the difference between an original color  $RGB(i)$  of a pixel  $i$  and this color can be calculated as  $|R(i)-R_p| + |G(i)-G_p| + |B(i)-B_p|$ . The search for the closest CLUT color to the original color of a pixel can be performed by systematically scanning the entire look-up table, but can also be performed by means of faster search algorithms, for example, a search algorithm taking the successive median colors between the closest colors obtained in the look-up table for the preceding evaluations of the same pixel while however determining, for each evaluation, the sign of the difference. Once it has determined the CLUT color which is closest to the original color of a pixel, evaluation circuit 8 selects this CLUT color (CLUT( $RGB(i)$ )) by associating with pixel  $i$  the address of this color in the color look-up table. As indicated previously, the color look-up table includes a reduced number of colors. The address of the CLUT colors thus comprises a reduced number of bits. By replacing for each pixel of an image the code of its original color by such an address, the memory size of the digital image is substantially reduced. As an example, by associating with the colors coded over 24 bits of a digital image an address of a color of a color look-up table of 256 colors, coded over 8 bits, the size of this image is substantially divided by 3.

Fig. 3 very schematically shows a digital image 10 corresponding to digital image 2 of Fig. 1 after approximation of its colors. In the case shown, it is assumed that the CLUT colors that are closest to the original colors of pixels 0, 1, n and n+1 of image 2 respectively are the colors having codes F00, 1A0, 1A0 and CA0. Evaluation circuit 8 associates CLUT color F00 with original color F11 of pixel 0, CLUT color 1A0 with original colors 1A1 of pixel 1 and 1B0 of pixel n, and CLUT color CA0 with original color CE0 of pixel n+1.

It should be noted that such an approximation method results in a loss of information by associating with several different original colors the same CLUT color. Thus, it eliminates from an image the color blendings that may be present, and it creates uniform color areas abruptly separated from one another. This phenomenon is particularly disturbing, for example, when the digital image includes areas such as a face, including many blendings of flesh color of different shades, exhibiting a low contrast with respect to one another. The previously-described approximation of the colors of a face conventionally displays a reduced number of areas with a strong contrast between one another, which is not very attractive.

Such a problem can be attenuated by a judicious choice of the color look-up table. In the preceding example, this amounts to storing in the CLUT a sufficient number of shades of flesh color to enable a convenient approximation of the color blendings in a face. However, such a solution is not always implementable, the CLUT size being limited.

Another known solution to attenuate the contrast between the color areas created by the preceding approximation method consists of artificially mixing the colors of the pixels located at the border of the areas of same color in the image. Thereby, after approximation, the separation border between the color areas is no longer clear, but has the aspect of a cloud of points. The human eye mixes the colors of the points of this cloud into a homogeneous color and it accepts this recomposed color as being an intermediary color between the two color areas. This mixing of the border pixel color is performed by adding a correction term to the original color of each pixel before its approximation. This

correction term is a function of the evaluation errors of the preceding pixels, each assigned with predetermined weighting coefficients.

Fig. 4 schematically shows the preceding pixels  $i-1$ ,  $i-n-1$ ,  $i-n$  and  $i-n+1$  conventionally used for approximating the original color of a pixel  $i$  of an image 2. It should be noted that pixel  $i-n$  represents a pixel of the preceding line, of same abscissa as  $i$ . In known solutions, it has been determined that correction term  $E(i)$ , added to original color  $RGB(i)$  of pixel  $i$  for its approximation must, to obtain an acceptable result, be equal to:

$$K1.ERR(i-1) + K2.ERR(i-n-1) + K3.ERR(i-n) + K4.ERR(i-n+1),$$

where  $K1$ ,  $K2$ ,  $K3$  and  $K4$  are predetermined fixed coefficients, and where  $ERR(i-1)$ ,  $ERR(i-n-1)$ ,  $ERR(i-n)$ , and  $ERR(i-n+1)$  correspond to the error approximations calculated for pixels  $i-1$ ,  $i-n-1$ ,  $i-n$ , and  $i-n+1$ . In other words,

$$ERR(i) = |RGB(i) + E(i) - CLUT(RGB(i) + E(i))|.$$

To obtain good results, the coefficients generally are the following:  $K1 = 7/16$ ,  $K2 = 1/16$ ,  $K3 = 5/16$ , and  $K4 = 3/16$ .

Such a method amounts to adding, to the future values of the four pixels adjacent to the current pixel:  $7/16$  of the current error to the right-hand pixel ( $i+1$ ),  $3/16$  of the error to the lower left-hand pixel ( $i+n-1$ ),  $5/16$  of the error to the lower pixel ( $i+n$ ), and  $1/16$  of the error to the lower right-hand pixel ( $i+n+1$ ).

A first disadvantage of the above conventional method is that it requires, for the processing of each pixel, effecting four multiplications to weight the evaluation errors of the preceding pixels, and four additions to calculate the correction term. These multiplications and additions are effected on codes having the length of the codes of the original pixel color, that is, including a large number of bits. Thus, such operations are relatively complex to implement, in particular in an integrated circuit.

A second disadvantage is that, to process a pixel of an image line, it is necessary to store in the memory the evaluation errors of three preceding pixels located on the preceding image line. Thus, this approximation method requires permanently



memorizing the approximation errors calculated for the pixels of the entire preceding line. These approximation errors must be stored in a specific memory, which increases the complexity of a circuit intended for implementing this method.

## SUMMARY OF THE INVENTION

5           An embodiment of the present invention overcomes the disadvantages of known solutions. The embodiment provides a solution for approximating the original color of the pixels of a digital image that only requires a small number of calculations and that does not require keeping in memory the approximation errors of the preceding line.

          The embodiment obtains visually acceptable images, by means of a method  
10   that is simple to implement in an integrated circuit.

          An embodiment of the present invention also provides a circuit for implementing such a method.

          The method approximates the respective colors of pixels of a digital image by selecting, from a look-up table and successively for each pixel of the image, a color, the  
15   code of which comes close with the smallest error to the sum of the code of the current pixel color and of a correction term, in which the correction term is equal to the smallest error calculated upon approximation of a preceding pixel, assigned with a weighting coefficient depending on the position of the current pixel in the image.

          According to an embodiment of the present invention, the weighting  
20   coefficient is a function of the respective least significant bits of binary codes representing the abscissa and the ordinate of the position of the current pixel.

          According to an embodiment of the present invention, the weighting coefficient is chosen from among a first and a second value when the least significant bit of the abscissa of the position of the current pixel is null and when respectively, the least  
25   significant bit of the ordinate of the position of the current pixel is null or equal to one, and from among a third and a fourth value when the least significant bit of the abscissa of the position of the current pixel is equal to one and when respectively, the least significant bit of the ordinate of the current pixel position is null or equal to one.

According to an embodiment of the present invention, the first value is equal to 0.25, the second value is equal to 1.00, the third value is equal to 0.75, and the fourth value is equal to 0.50.

According to an embodiment of the present invention, the image is scanned  
5 line by line, and the correction term is null for the first pixel of each line.

An embodiment of the present invention also provides an electronic circuit that includes means for implementing any of the embodiments of the preceding approximation method.

According to an embodiment of the present invention, the electronic circuit  
10 includes a memory in which are stored the codes of the colors of the look-up table, an evaluation circuit, a first input of which is intended for receiving a color code from the memory and a second input of which receives a corrected code, for selecting the stored color, the code of which comes close with the smallest error to the corrected code and for  
15 generating a correction term equal to the difference between the selected stored color and the corrected code, and a correction circuit for generating the corrected code, equal to the sum of the code of the color of a current pixel and of the correction term, assigned with the weighting coefficient.

The foregoing objects, features and advantages of the present invention, will  
be discussed in detail in the following non-limiting description of specific embodiments in  
20 connection with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1 to 4, previously described, are intended for showing the state of the art and the problem to solve;

Fig. 5 schematically shows the pixels taken into account in an error  
25 distribution approximation method according to an embodiment of the present invention;  
and

Fig. 6 schematically shows a circuit intended for implementing a color approximation method according to an embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

For clarity, the same elements have been designated by the same references in the different drawings.

5 A feature of the present invention is that it provides calculating by means of a coefficient, the value of which is a function of the pixel abscissa and ordinate in the image, a correction term added to the original color of each pixel, upon its approximation.

Another feature of the present invention is that the correction term, added to the original color of each pixel before approximation, is calculated based on the approximation error of a single pixel, immediately preceding the current pixel.

10 Fig. 5 schematically shows pixels  $i$  and  $i-1$ , used according to an embodiment of the present invention to calculate the correction term added to the original color of current pixel  $i$ . Keeping the previously used notations, the approximation error calculated for the pixel  $i-1$  preceding pixel  $i$  is called  $ERR(i-1)$ . This error preferably corresponds to the modulus of the difference between the code of the original color plus the  
15 correction term and the code of the closest color in the color look-up table. According to the embodiment of Fig. 5, the approximation of original color  $RGB(i)$  of pixel  $i$  is performed by searching, in the look-up table, the closest color to the sum of  $RGB(i)$  and of a correction term  $E'(i)$ , where  $E'(i) = k' \cdot ERR(i-1)$ .

20 Coefficient  $k'$  is, according to a preferred embodiment of the present invention, determined by means of the following truth table

$pf(X(i))$	0 0 1 1
$pf(Y(i))$	0 1 0 1
$k'$	$k_1 k_2 k_3 k_4$ ,

25 where  $pf(X(i))$  and  $pf(Y(i))$  respectively designate the least significant bit of a binary code respectively representing abscissa  $X(i)$  and ordinate  $Y(i)$  of pixel  $i$ .

Thus, the weighting coefficient is a function of the position of the pixel in the image but is the same for all the pixels having abscissa and ordinate binary codes with the same least significant bits.

The present inventors have determined that the following values may advantageously be used:

$$k1 = 0.25$$

$$k2 = 1.00$$

5  $k3 = 0.75$

$$k4 = 0.50.$$

The pixels of a digital image are, preferably and as previously, sequentially processed, line after line. Preferably, the correction term of the first pixel of each line is null, since the pixel preceding a line beginning pixel is not its neighbor in the image. It should be noted that according to the preferred embodiment of the present invention, the approximation method includes a single addition and a single multiplication for the calculation of the correction term, and that it only requires memorizing the approximation error of the pixel preceding the current pixel. Thus, this method will be particularly simple to implement in an electronic circuit.

15 Fig. 6 schematically shows a circuit 12 for implementing the method just described. Circuit 12 includes a memory 6 (MEM) connected to a first input of an evaluation circuit 8 (EVAL). A correction circuit 14 (REDIS) has a first input connected for successively receiving the color of each pixel, and a second input connected for receiving the evaluation error  $ERR(i)$  made by evaluation circuit 8 upon evaluation of each pixel  $i$ .

20 Blocks with no reference also illustrate the data associated with the inputs-outputs of elements 6, 8, and 14 for a pixel  $i$  provided to circuit 12. For each pixel  $i$ , correction circuit 14 provides evaluation circuit 8 with the sum of the original color  $RGB(i)$  of pixel  $i$  and of the correction term  $E'(i)$  calculated based on evaluation error  $ERR(i-1)$  of the preceding pixel  $i-1$ , with  $E'(i) = k'.ERR(i-1)$ ,  $k'$  having been previously defined. Evaluation circuit 8 associates to this sum the look-up table color  $CLUT(RGB(i) + E'(i))$ , the color of which comes close with the smallest error. Approximation error  $ERR(i)$  provided by evaluation circuit 8 to redistribution circuit 14 for the next pixel is this smallest error.

Of course, the present invention is likely to have various alterations, modifications, and improvements which will readily occur to those skilled in the art. For example, a method in which the weighting coefficient used to calculate correction term  $E'(i)$  of a pixel  $i$  is selected from among four values according to the least significant bit of the codes of the abscissa and ordinate of this pixel has been discussed, but a greater number of weighting coefficients may also be used, for example sixteen values selected according to the two least significant bits of the abscissa and ordinate. Further, the present invention has been described in relation with RGB-coded colors, for which the distance between two colors can be evaluated by calculating the sum of the absolute values of the differences of the RGB components of the two colors, but those skilled in the art will easily adapt the present invention to colors coded differently.

Such alterations, modifications, and improvements are intended to be part of this disclosure, and are intended to be within the spirit and the scope of the present invention. Accordingly, the foregoing description is by way of example only and is not intended to be limiting. The present invention is limited only as defined in the following claims and the equivalents thereto.

## CLAIMS

What is claimed is:

1. A method of approximation of respective colors of pixels of a digital image, the method comprising selecting, from a look-up table and successively for each pixel, a color having a code which comes close with the smallest error to the sum of the code of a current pixel color and of a correction term, wherein the correction term is equal to the smallest error calculated upon approximation of a preceding pixel, assigned with a weighting coefficient depending on the position of the current pixel in the image.

2. The method of claim 1, wherein the weighting coefficient is a function of respective least significant bits of binary codes representing an abscissa and an ordinate of the position of the current pixel.

3. The method of claim 2, wherein the weighting coefficient is chosen:  
from among a first and a second value when the least significant bit of the abscissa of the position of the current pixel is null and when respectively, the least significant bit of the ordinate of the position of the current pixel is null or equal to one, and

from among a third and a fourth value when the least significant bit of the abscissa of the position of the current pixel is equal to one and when respectively, the least significant bit of the ordinate of the position of the current pixel is null or equal to one.

4. The method of claim 3, wherein:  
the first value is equal to 0.25,  
the second value is equal to 1.00,  
the third value is equal to 0.75, and  
the fourth value is equal to 0.50.

5. The method of claim 1, wherein the image is scanned line by line, and the correction term is null for the first pixel of each line.

6. An electronic circuit for approximating the respective colors of pixels of a digital image, including means for implementing the method of claim 1.

7. The electronic circuit of claim 6, wherein the means include:

a memory in which are stored codes of colors of the look-up table, coded in the same way as the pixel colors;

an evaluation circuit having a first input that receives a color code from the memory and a second input that receives the code of a pixel of the image plus a correction term, the evaluation circuit selecting the stored color having the code that comes close with the smallest error; and

a correction circuit, an input of which is connected to an output of the evaluation circuit, for generating a corrected code, equal to the sum of the code of the color of a current pixel and of the correction term.

8. A method of compressing a digital image having pixels each with a color represented by a color code, the method comprising:

selecting, for a current one of the pixels of the digital image, one of a plurality of weighting coefficients based on a position of the current pixel;

computing a sum of a correction term and a color code of the current pixel, the correction term being equal to an error value computed for a previous one of the pixels multiplied by the selected weighting coefficient for the current pixel;

selecting for the current pixel an estimated color from a plurality of estimated colors, the selected estimated color being the estimated color that most closely matches the computed sum; and

replacing the color code of the current pixel with the selected estimated color.

9. The method of claim 8, further comprising computing for the current pixel an error value equal to a difference between the computed sum and the color code for the current pixel and using the computed error value for the current pixel to compute a correction term for a subsequent one of the pixels.

10. The method of claim 8 wherein the position of the current pixel has an ordinate value with a first least significant bit and an abscissa value with a second least significant bit and the selected weighting coefficient is selected as a function of the first and second least significant bits.

11. The method of claim 10 wherein selecting the weighting coefficient for the current pixel includes:

selecting from among a first and a second value when the first least significant bit is null and when respectively, the second least significant bit is null or equal to one; and

selecting from among a third and a fourth value when the first least significant bit is equal to one and when respectively, the second least significant bit is null or equal to one.

12. The method of claim 11 wherein:

the first value is equal to 0.25;

the second value is equal to 1.00;

the third value is equal to 0.75; and

the fourth value is equal to 0.50.

13. The method of claim 8 wherein the digital image is scanned line by line, and the correction term is null for a first pixel of each line.

14. The method of claim 8 wherein the weighting coefficient selected for the current pixel is not selected for any pixels that are immediately adjacent to the current pixel.



15. A method of compressing a digital image having pixels each with a color represented by a color code, the method comprising:

assigning a first correction coefficient to each pixel of a first group of pixels in the digital image;

assigning a second correction coefficient to each pixel of a second group of pixels in the digital image;

for each of the pixels of the first group, selecting an estimated color of a plurality of estimated colors, the selected estimated color being selected based on the color of the pixel and the first correction coefficient; and

for each of the pixels of the second group, selecting an estimated color of the plurality of estimated colors, the selected estimated color for the pixel being selected based on the color of the pixel and the second correction coefficient.

16. The method of claim 15 wherein the pixels of the first group are not contiguous with each other and the pixels of the second group are not contiguous with each other.

17. The method of claim 15 wherein the step of selecting an estimated color for each pixel of the first group includes, for each pixel of the first group, computing a sum of a correction term and a color code of the pixel, the correction term being equal to an error value computed for a previous one of the pixels of the digital image multiplied by the first correction coefficient; the selected estimated color for the pixel being the estimated color that most closely matches the computed sum.

18. The method of claim 17, further comprising, for each pixel of the first group, computing an error value equal to a difference between the computed sum for the pixel and the color code for the pixel and using the computed error value for the pixel to compute a correction term for a subsequent one of the pixels of the digital image.

19. The method of claim 15 wherein the pixels of the first group alternate with the pixels of the second group in the digital image.

20. The method of claim 15, further comprising:

assigning a third correction coefficient to each pixel of a third group of pixels in the digital image;

assigning a fourth correction coefficient to each pixel of a fourth group of pixels in the digital image;

for each of the pixels of the third group, selecting an estimated color of the plurality of estimated colors, the selected estimated color for the pixel being selected based on the color of the pixel and the third correction coefficient; and

for each of the pixels of the fourth group, selecting an estimated color of the plurality of estimated colors, the selected estimated color for the pixel being selected based on the color of the pixel and the fourth correction coefficient, wherein the pixels of the first and second groups alternate with each other in a first line of the digital image and the pixels in the third and fourth groups alternate with each other in a second line of the digital image, the second line being immediately adjacent to the first line.

ERROR DISTRIBUTION FOR THE APPROXIMATION OF THE  
PIXEL COLOR OF A DIGITAL IMAGE

ABSTRACT

A method of approximation of the respective colors of pixels of a digital image by selecting, from a look-up table and successively for each pixel of the image, a color, the code of which comes close with the smallest error to the sum of the code of the current pixel color and of a correction term, in which the correction term is equal to the smallest error calculated upon approximation of a preceding pixel, assigned with a weighting coefficient depending on the position of the current pixel in the image.

L:\85x063 - stm\859063\478\478-AP.doc




Fig 1  
(Prior Art)




Fig 2  
(Prior Art)







Fig 3  
(Prior Art)



Express Mail No.: EL615483535US

# Declaration and Power of Attorney for Patent Application

## *Déclaration et Pouvoirs pour Demande de Brevet*

### French Language Declaration

En tant que l'inventeur nommé ci-après, je déclare par le présent acte que:

As a below named inventor, I hereby declare that:

Mon domicile, mon adresse postale et ma nationalité sont ceux figurant ci-dessous à côté de mon nom.

My residence, post office address and citizenship are as stated below next to my name.

Je crois être le premier inventeur original et unique (si un seul nom est mentionné ci-dessous), ou l'un des premiers co-inventeurs originaux (si plusieurs noms sont mentionnés ci-dessous) du sujet revendiqué, pour lequel une demande de brevet a été déposée concernant l'invention intitulée:

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

ERROR DISTRIBUTION FOR THE APPROXIMATION OF THE PIXEL COLOR OF A DIGITAL IMAGE

et dont les caractéristiques sont fournies ci-joint à moins que la case suivante n'ait été cochée:

the specification of which is attached hereto unless the following box is checked:

☐ a été déposée le \_\_\_\_\_  
sous le numéro de Demande des Etats-Unis ou  
le Numéro de demande international PCT  
\_\_\_\_\_ et modifiée le \_\_\_\_\_  
(le cas échéant).

☐ was filed on \_\_\_\_\_  
as United States Application Number or PCT  
International Application Number \_\_\_\_\_ and was  
amended on \_\_\_\_\_ (if  
applicable).

Je déclare par le présent acte avoir passé en revue et pris connaissance du contenu des caractéristiques ci-dessus, revendications comprises, telles que modifiées par tout amendement dont il aura été fait référence ci-dessus.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

Je reconnais devoir divulguer toute information pertinente à l'examen de cette demande, comme le définit le Titre 37, § 1.56 du Code fédéral des réglementations.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

## French Language Declaration

Je revendique par le présent acte avoir la priorité étrangère, en vertu du Titre 35, § 119 du Code des Etats-Unis, sur toute demande étrangère de brevet ou certificat d'inventeur figurant ci-dessous et ai aussi pris connaissance de toute demande étrangère de brevet ou de tout certificat d'inventeur ayant une date de dépôt précédant celle de la demande à propos de laquelle une priorité est revendiquée.

I hereby claim foreign priority under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior foreign applications  
Demande(s) de brevet antérieure(s)

Priority claimed  
Droit de priorité revendiqué

99/11607 FRANCE 14 SEPTEMBER 1999  
(Number) (Country) (Day/Month/Year Filed)  
(Numéro) (Pays) (Jour/Mois/Année de dépôt)

☒
☐

Yes  
Oui

No  
Non

(Number) (Country) (Day/Month/Year Filed)  
(Numéro) (Pays) (Jour/Mois/Année de dépôt)

☐

Yes  
Oui

No  
Non

(Number) (Country) (Day/Month/Year Filed)  
(Numéro) (Pays) (Jour/Mois/Année de dépôt)

☐

Yes  
Oui

No  
Non

Je revendique par le présent acte tout bénéfice, en vertu du Titre 35, § 120 du Code des Etats-Unis, de toute demande de brevet effectuée aux Etats-Unis figurant ci-dessous et, dans la mesure où le sujet de chacune des revendications de cette demande de brevet n'est pas divulgué dans la demande américaine préalable, en vertu des dispositions du premier paragraphe du Titre 35, § 112 du Code des Etats-Unis, je reconnais devoir divulguer toute information pertinente à la demande de brevet comme défini dans le Titre 37, § 1.56 du Code fédéral des réglementations, dont j'ai pu disposer entre la date de dépôt de la première demande et la date de dépôt de la demande nationale ou PCT internationale:

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56, which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)  
(No. de série de la demande)

(Filing Date)  
(Date de dépôt)

(Statut)  
(breveté, en attente, annulé)

(Status)  
(patented, pending,  
abandoned)

(Application Serial No.)  
(No. de série de la demande)

(Filing Date)  
(Date de dépôt)

(Statut)  
(breveté, en attente, annulé)

(Status)  
(patented, pending,  
abandoned)

Je déclare par le présent acte que toute déclaration ci-incluse est, à ma connaissance, véridique et que toute déclaration formulée à partir de renseignements ou de suppositions est tenue pour véridique; et de plus, que toutes ces déclarations ont été formulées en sachant que toute fausse déclaration volontaire ou son équivalent est passible d'une amende ou d'une incarcération, ou des deux, en vertu de la Section 1001 du Titre 18 du Code des Etats-Unis et que de telles déclarations volontairement fausses risquent de compromettre la validité de la demande de brevet ou du brevet délivré à partir de celle-ci.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## French Language Declaration

**POUVOIRS:** En tant que l'inventeur cité, je désigne par la présente l'(les) avocat(s) et/ou agent(s) suivant(s) pour qu'il(s) poursuive(nt) la procédure de cette demande de brevet et traite(nt) toute affaire avec le Bureau des brevets et marques s'y rapportant. (mentionner le nom et le numéro d'enregistrement)

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Richard W. Seed, Reg. No. 16,557  
Robert J. Baynham, Reg. No. 22,846  
George C. Rondeau, Jr., Reg. No. 28,893  
David H. Deits, Reg. No. 28,066  
William O. Ferron, Jr., Reg. No. 30,633  
David J. Maki, Reg. No. 31,392  
Richard G. Sharkey, Reg. No. 32,629  
David V. Carlson, Reg. No. 31,153  
Karl R. Hermanns, Reg. No. 33,507  
David D. McMasters, Reg. No. 33,963  
Michael J. Donohue, Reg. No. 35,859

Jane E.R. Potter, Reg. No. 33,332  
Robert Iannucci, Reg. No. 33,514;  
Lorraine Linford, Reg. No. 35,939  
David W. Parker, Reg. No. 37,414  
Ellen M. Bierman, Reg. No. 38,079  
Ann T. Kadlecsek, Reg. No. 39,244  
E. Russell Tarleton, Reg. No. 31,800  
Kevin S. Costanza, Reg. No. 37,801  
Thomas E. Loop, Reg. No. 42,810  
Stephen J. Rosenman, Reg. 43,058  
Brian L. Johnson, Reg. No. 40,033  
Susan D. Betcher, Reg. No. 43,498

William T. Christiansen, Reg. No. 44,614  
Gary M. Myles, Reg. No. 46,209  
Eric J. Gash, Reg. No. 46,274

Lisa K. Jorgenson, Reg. No. 34,845  
Robert D. McCutcheon, Reg. No. 38,717  
Jeffrey D. Moy, Registration No. 39,307  
Theodore E. Galanthay, Reg. No. 24,122

Adresser toute correspondance à:



Send Correspondence to:

Seed Intellectual Property Law Group PLLC  
701 Fifth Avenue, Suite 6300  
Seattle, Washington 98104-7092  
U.S.A.

Adresser tout appel téléphonique à: (nom et numéro de téléphone)

Direct Telephone Calls to: (name and telephone number)

(206) 622-4900


Nom complet de l'unique ou premier inventeur LAURY Marc	Full name of sole or first inventor	
Signature de l'inventeur  Date 28/08/2000	Inventor's signature	Date
Domicile 38100 GRENOBLE, FRANCE	Residence	
Nationalité French	Citizenship	
Adresse postale 11, Rue Charles Péguy	Post Office Address	
Nom complet du second co-inventeur, le cas échéant SEIGNERET Franck	Full name of second joint inventor, if any	
Signature du second inventeur  Date 29/08/2000	Second Inventor's signature	Date
Domicile 38140 RIVES, FRANCE	Residence	
Nationalité French	Citizenship	
Adresse postale 426, Rue Taillefer	Post Office Address	

(Fournir les mêmes renseignements et la signature de tout co-inventeur supplémentaire.)

(Supply similar information and signature for third and subsequent joint inventors.)



## French Language Declaration

Nom complet de l'unique ou premier inventeur CHIARUZZI Emmanuel	Full name of third inventor, if any
Signature de l'inventeur  Date 31/08/2000	Third Inventor's signature Date
Domicile 38000 GRENOBLE, FRANCE	Residence
Nationalité French	Citizenship
Adresse postale 8, Rue Jean Prévost	Post Office Address
Nom complet du second co-inventeur, le cas échéant	Full name of fourth joint inventor, if any
Signature du second inventeur Date	Fourth Inventor's signature Date
Domicile	Residence
Nationalité	Citizenship
Adresse postale	Post Office Address
Nom complet du second co-inventeur, le cas échéant	Full name of fifth joint inventor, if any
Signature du second inventeur Date	Fifth Inventor's signature Date
Domicile	Residence
Nationalité	Citizenship
Adresse postale	Post Office Address
Nom complet du second co-inventeur, le cas échéant	Full name of sixth joint inventor, if any
Signature du second inventeur Date	Sixth Inventor's signature Date
Domicile	Residence
Nationalité	Citizenship
Adresse postale	Post Office Address